



Identification	Part No.	Drawing	Dimensions in mm
<p>Fibre optic cable, double ended, single mode, metal 2 x Han® 3 A, 2 x LC duplex</p> <p>Length: a = 1 m a = 5 m a = 10 m a = 20 m a = 40 m a = 50 m a = 100 m</p>	<p>33 54 211 0010 001 33 54 211 0050 001 33 54 211 0100 001 33 54 211 0200 001 33 54 211 0400 001 33 54 211 0500 001 33 54 211 1000 001</p>	<p>double ended</p> <p>a = length</p>	
<p>Fibre optic cable, single ended, single mode, metal 1 x Han® 3 A, 2 x LC duplex</p> <p>Length: a = 1 m a = 5 m a = 10 m a = 20 m a = 40 m a = 50 m a = 100 m</p>	<p>33 54 111 0010 001 33 54 111 0050 001 33 54 111 0100 001 33 54 111 0200 001 33 54 111 0400 001 33 54 111 0500 001 33 54 111 1000 001</p>	<p>Protection level: IP 65 / IP 67</p> <p>single ended</p> <p>a = length</p>	
<p>Fibre optic breakout cable, single mode</p> <p>Length: 10 m Length: 20 m Length: 100 m</p>	<p>33 54 751 0100 001 33 54 751 0200 001 33 54 751 1000 001</p>	<p>PVC jacket 4-fibre single mode Outer diameter: 9.5 mm Min. bending radius: Installation: 15 x OD Operating: 10 x OD</p>	

Further cable lengths are available on request