



## DUAL BAND 802.11 a/b/g/n SPATIAL DIVERSITY ANTENNA

Laird's S24493D antenna offers the system integrator a spatial diversity antenna system that will accommodate all applications and modes in both the 2.4-2.5 GHz and 5.15-5.875 GHz bands. This one diminutive aesthetically neutral package covers every single-band and multi-band multi-mode application that you might be confronted with in the field.

The design also provides flexibility for future changes in deployed system modes. In place of spatial diversity, each port can be used individually to support 802.11b/g and 802.11a systems simultaneously for dual-band non-diversity deployments.

The radiation patterns are uniform and symmetrical, providing high levels of signal density into defined coverage zones. This is critical for high data rate, high-capacity configurations. Mounting options allow either flush surface ceiling mount with supplied ceiling clips (S24493DS) or mast mount (S24493DM) with pole mounting hardware.

### FEATURES

- 802.11 a/b/g/n and wide band frequency coverage
- Variety of cable lengths and connectors available
- Fast and easy installation with either ceiling clips / mast mount
- Neutral color and diminutive profile disappears into the environment

### MARKETS

- Hospital
- Campus
- Research Institute
- Public safety wireless systems
- Transport Terminals

PARAMETER	SPECIFICATION
Antenna Part Number	S24493DS / S24493DM
Frequency Range (GHz)	2.4 - 2.5 & 4.90 - 5.99 GHz
Gain (dBi) w/36" cable	(3) @ 2.5 / (4) @ 5.5 GHz
3 dB Beamwidth - Elevation	60° @ 2.5 / 58° @ 5.5 GHz
3 dB Beamwidth - Azimuth	Omnidirectional
Polarization	Linear Vertical
VSWR	2.0:1
Pigtail (in)	36
RF connector	Reverse TNC / type N (m)
Power Rating (watts)	2
Dimensions in. (mm)	6.16x3.66x.89 (156x93x22)
Weight (kg)	.23 kg
Operational Temperature (C°)	0° to +55°
Mount style	Ceiling tile / mast

Americas: +1.847.839.6907  
IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941  
IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127  
IAS-AsiaSales@lairdtech.com

[www.lairdtech.com](http://www.lairdtech.com)

Laird warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations Laird will, at its option, either repair or replace any part of its products that prove defective by reason of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the Laird product is installed. Useful lifetime of the original end product may vary but is not to exceed five (5) years from the original date of the end product purchase.

ANT-DS-S24493D 0715

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.

