

Specification Sheet

Part Number: 170-03089



Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Black, 1000 ft/bulk reel

Article Number

170-03089

Type

BSPFR180B

Color

Black (BK)

Features & Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Quantity Per

reel

Product Description

A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description

Braided Sleeving, Expandable, Flame Retardant, .125" Dia, PET, Black, 1000 ft/bulk reel

Global Part Name

BSPFR180B-PET-BK

Length L (Imperial)

1000.0

Length L (Metric)

304.8

Bundle Diameter Min (Imperial)

0.094

Bundle Diameter Min (Metric)

2.4

Bundle Diameter Max (Imperial)

0.25

Bundle Diameter Max (Metric)

6.4

Diameter D (imperial)

0.13

Diameter D (metric)

3.2

Nominal Diameter (Imperial)

1/8

Nominal Diameter (Metric)

3.2

Material

Polyester (PET)

Material Shortcut

PET

Flammability

UL VW-1 FAR 25 UL 94 V0 Mil-202 FMVSS 302

Halogen free Yes

Operating Temperature (Metric) -94°F to +257°F (-70°C to +120°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB UL 94 VW-1

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity(Imperial) 1000

Package Quantity (Metric) 304.80

Customs Number 3926909987

Weight (Metric) 0.73

Weight (Imperial) 1.6