


HC-HV 3-TFL-45/M1PG16G

Order No.: 1773514

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1773514>

Sleeve housing, for single locking latch, height 45 mm, with screw connection, 1x Pg16, straight cable entry

Commercial data

GTIN (EAN)	 4 017918 103668
Note	Made-to-order
sales group	D003
Pack	10 pcs.
Customs tariff	85389099
Catalog page information	Page 244 (PC-2005)

Product notesWEEE/RoHS-compliant since:
03/01/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General data**

Note	For contact inserts HV-HV3
Design	HV3
Height	45 mm
Width	43 mm
Length	73 mm
Housing type	Sleeve housings
Locking type	for single locking latch

Cable exit	Straight
Type of the screw connection	1x Pg16
Pg screw connection	With
Wrench size, union nut	22 mm
External cable diameter	7.5 mm ... 15 mm
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C
Housing material	Aluminum, die-cast
Housing surface material	Powder-coated, gray
Cable gland material	Nickel-plated brass
Cable seal material	NBR

Certificates / Approvals



Certification

GOST

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2010 Phoenix Contact
Technical modifications reserved;