


VAC13KS, South Africa, V-Lock cord retaining, 1.5 m, Connector IEC C13, H05VV-F3G0.75, black



**Description**

- Power Cord ,
- Protection class I , Pin temperature 70 °C ,
- with V-Lock interlocking system

**Technical Data**

|                                 |   |                         |  |
|---------------------------------|---|-------------------------|--|
| Ratings IEC                     | 10A / 250VAC; 50Hz  | appliance inlet/-outlet | C13 acc. to IEC 60320-1  |
| Dielectric Strength             | > 2kVDC between L-N<br>> 2kVAC between L/N-PE<br>(1 min/50Hz)     |                         | (for cold conditions) pin-temperature 70 °C, 10A, Protection Class I |
| Allowable Operation Temperature | -25 °C to 70 °C   |                         |  |
| IP-Protection                   | from front side IP 20 acc. to IEC 60529                           |                         |  |
| Insulation cover                | Suitable for appliances with protection class I acc. to IEC 61140 |                         |  |
| Terminal                        | moulded   |                         |  |
| Material: Housing               | PVC, black  |                         |  |

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [General Product Information](#)

**All Variants**

| Connector |        |               |                          |            |       | cable        |         |            |          |       | Plug |  |  |  |  | Order Number |
|-----------|--------|---------------|--------------------------|------------|-------|--------------|---------|------------|----------|-------|------|--|--|--|--|--------------|
| Type      | V-Lock | Cord Type     | Conductor cross section  | Length [m] | Color | Type         | Country | Standard   | Style    | Index |      |  |  |  |  |              |
| C13       | ●      | H05VV-F3G0.75 | 3 x 0.75 mm <sup>2</sup> | 1.5        | black | South Africa | ZA      | SANS 164-1 | straight | -     |      |  |  |  |  | 6051.2078    |

Availability for all products can be searched real-time: <http://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

**Packaging unit** 50 Pcs

**Mating Inlets/Plugs shuttered**

**Category / Description**

[Appliance Inlet Overview complete](#)



|  |      |
|--|------|
| 6010, Mounting: Snap-in, Solder, quick-connect, screw, PCB, Appliance Inlet: IEC C14   | 6010 |
| 6015, Mounting: Snap-in, Solder, quick-connect, screw, PCB, Appliance Inlet: IEC C18   | 6015 |
| 6048, Mounting: Screw, Appliance Inlet: IEC C14  | 6048 |
| 6061, Mounting: Screw, Appliance Inlet: IEC C14  | 6061 |
| GSP1, Mounting: Screw, Appliance Inlet, IEC C14, For PCB mounting, IP 40, Quick connect terminals 4.8 x 0.8 mm angled or straight, Suitable for appliances with protection class I or II | GSP1 |
| <a href="#">Appliance Inlet further types to 6051.2078</a>   | ...  |

## IEC Inlet Filter Overview complete



|   |      |
|---|------|
| 5120, Mounting: Screw, Front-/Rear-Side, Filter: Standard and Medical Version, Without fuse holder: 10 A, Themoplast / steel tin-plated Appliance Inlet: IEC C14, Suitable for appliances with protection class I or II       | 5120 |
| 5123, Mounting: Screw, Front-/Rear-Side, Filter: Standard and Medical Version, Without fuse holder: 10 A, Themoplast / steel tin-plated Appliance Inlet: IEC C14, Suitable for appliances with protection class I or II       | 5123 |
| 5150, Mounting: Screw, Front-/Rear-Side, Filter: Standard, medical and industrial version, Without fuse holder: 10 A, Themoplast / steel tin-plated Appliance Inlet: IEC C14, Suitable for appliances with protection class I | 5150 |
| KFS, Mounting: Screw, Front Side, Filter: Standard Version, Without fuse holder: 10 A, Appliance Inlet: IEC C14, pre-wired  | KFS  |

[IEC Inlet Filter further types to 6051.2078](#)

## Power Entry Module Overview complete



|  |      |
|--|------|
| DC11, Mounting: Screw, Rocker switch: non-illuminated or illuminated 1 or 2 pole, Quick connect terminals 4.8 x 0.8 mm, Appliance Inlet: IEC C14, Without fuse holder: Suitable for appliances with protection class I or II   | DC11 |
| DC21, Mounting: Screw Rear Side, Rocker switch: non-illuminated or illuminated 2-pole, Quick connect terminals 4.8 x 0.8 mm Appliance Inlet: IEC C14, Without fuse holder:   | DC21 |
| DD11, Mounting: Screw-on mounting, Rocker switch: non-illuminated or illuminated 2-pole, Quick connect terminals 4.8 x 0.8 mm, Appliance Inlet: IEC C14, With or without protection cover, Fuse holder: 1 or 2 pole, Suitable for appliances with protection class I | DD11 |
| DD21, Mounting: Screw-on mounting Rear Side, Rocker switch: non-illuminated or illuminated 2-pole, additional quick connect 4.8 x 0.8 mm Appliance Inlet: IEC C14, Fuse holder: 1 or 2 pole  | DD21 |
| KD, Mounting: Screw, Quick connect terminals 4.8 x 0.8 mm, voltage selector: 2-4 digits, Fuse holder: 1 or 2 pole, Rocker switch, non-illuminated, 2-pole, Appliance Inlet: IEC C14, 250 VAC, prewired, Suitable for appliances with protection class I              | KD   |

[Power Entry Module further types to 6051.2078](#)

## Power Entry Module with line filter Overview complete



|  |      |
|--|------|
| DC12, Mounting: Screw, Front-/Rear-Side, Filter, Standard and Medical Version, Without fuse holder: 10 A, Rocker switch: 1 or 2 pole, non-illuminated or illuminated Appliance Inlet: IEC C14, prewired                                      | DC12 |
| DC22 Mounting: Screw, Rear Side, PCB, 10 A, Filter: Standard and Medical Version, Without fuse holder: Rocker switch: 1 or 2 pole, non-illuminated or illuminated, Appliance Inlet: IEC C14, Suitable for appliances with protection class I | DC22 |
| DD12, Mounting: Screw-on mounting, Front Side, Filter, Standard and Medical Version, Fuse holder: 1 or 2 pole, 10 A, Rocker switch: 2-pole, non-illuminated Appliance Inlet: IEC C14, prewired   | DD12 |
| DD22 Mounting: Screw-on mounting, Rear Side, PCB, 10 A, Filter: Standard and Medical Version, Fuse holder: 1 or 2 pole, Rocker switch: 2-pole, non-illuminated, Appliance Inlet: IEC C14, Suitable for appliances with protection class I    | DD22 |
| CD, Mounting: Screw, Front Side, Filter: Standard and Medical Version, Fuse holder: 1 or 2 pole, Front Side, 10 A, 2-pole, voltage selector: step, 2-4 digits, Appliance Inlet: IEC C14, prewired  | CD   |

[Power Entry Module with line filter further types to 6051.2078](#)