



- NOTE:
1. MATERIAL: HIGH TEMP PLASTIC; UL94V-0
 2. FINISH: COPPER ALLOY
 3. SPEC.: GOLD AT CONTACT (40U") MIN NI OVER ALL G/F OVER Turn(40U") MIN NI OVER ALL
 4. THE HSG. WILL WITHSTAND EXPOSURE TO 280C PEAK TEMP. FOR 10 SEC. IN A CONNECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.
 5. MATING SIDE LENGTH: 2.50MM MIN.
 6. PRODUCT NUMBERING: 200218 3 5 - XXX XX X X LF
- LEAD FREE
- PLATING:
 1: G/F ALL OVER
 4: 0.25um(10U") GOLD AT CONTACT
 8: 0.76um(30U") GOLD AT CONTACT
- PACKING:
 T: TUBE
- PIN COUNT
 04, 06, 08, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42, 44, 46, 48, 50 (EVERY EVEN PIN)
- STACK HEIGHT "K"
 EXAMPLE: 045=4.5MM IN 0.5MM INCREMENT

Recommended P.C.B. Layout
 Layout Tolerance = ± 0.05 mm

mot'l. code		tolerances unless otherwise specified		CUSTOMER COPY		FCI	
ltr	ecn no	dr	dtte	linear	projection	title	www.fciconnect.com
A	-	S.LIN	11'-5-17	.XX ± 0.25 .XXX ± 0.15	MM	1.27X1.27MM BTB STACK HD VT, SMT	
				angles 0° ± 2°		product family 585	
				dr	STERLING LIN	size/ dwg no	
				engr	STERLING LIN	20021835	
				chr	STERLING LIN	code	
				oppl	GARY HSEH	TWN	
sheet	revision	A	-			sheet	
index	sheet	1	-			1 of 1	

1 | 2

ACAD

3 |

cage code

4

1 | 2

3 |

4