

Circular Fir Tree Push Mount Tie

Circular Fir Tree Push Mount Tie

HellermannTyton's Circular Fir Tree Push Mount Tie offers a simple and easy method for bundling and mounting cables, wires and hoses. The unique fir tree design of the push mount provides one mounting solution for a wide range of applications with various panel thicknesses. The tie is ideally suited for the mounting of wire harnesses in conventional panel holes, threaded holes, and blind assembly holes. The tie is also compatible with a series of HellermannTyton cable tie tools (MK7P, MK7, MKHT, MK9, and MK9HT) to provide an easy, safe and ergonomically friendly installation around the bundle.


Product Features

- Low mount insertion force reduces installation time and installer fatigue
- High mount extraction force ensures a secure fit of the bundle in its application
- Disc feature minimizes the ingress of dust, dirt, and water into the application mounting hole
- Outside serrations on the tie strap minimizes potential indentation or damage to the bundle
- Clamp rails on the tie head allow for a strong hold on the smallest of bundle diameters and on bundles protected with convoluted tubing.



Applications

- Automotive Wire Harnesses
- Truck & Heavy Duty Equipment Wire Harnesses
- Aerospace Wire Harnesses
- White Goods Equipment Wire Harnesses
- Solar Panel & Wind Power Wire Harnesses



Material Data	
Material	Polyamide 6.6 Heat Stabilized
Color	Black
Operating Temperature	-40°F (-40°C) to + 221°F (105°C) Continuous
Flammability	UL94 V2




Product Selection

Article No.	Part No.	Type	Min. Tensile Strength	Mounting Hole	Panel Thickness	Length (L)	Max Bundle	Width (W)	Color	Pkg. Qty
			lbs. (N)	in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)		
157-00108	157-00108	T50SOSFT6E2	40 (180)	.25"-.28" (6.3-7.0)	.028"-.27" (0.7-7.0)	6.49" (165)	1.37" (35)	.181" (4.6)	Black	1000
157-00097	157-00097	T50SOSFT6LGE	40 (180)	.25"-.28" (6.3-7.0)	.028"-.27" (0.6-4.2)	6.49" (165)	1.37" (35)	.181" (4.6)	Black	1000

Use Part No. for ordering and Type for specification

Circular Fir Tree Push Mount Tie

Detailed Product Description



HellermannTyton

HellermannTyton North American Corporate Headquarters

7930 N. Faulkner Rd, PO Box 245017
 Milwaukee, WI 53224-9517
 Phone: (414) 355-1130, (800) 537-1512
 Fax: (414) 355-7341, (800) 848-9866
 email: corp@htamericas.com
 www.hellermann.tyton.com

TS16949:2002, ISO 9001:2000, and ISO14001 Certified

HellermannTyton Canada

Unit #4, 205 Industrial Parkway North
 Aurora, Ontario L4G 4C4 Canada
 Phone: (800) 661-2461
 Fax: (800) 390-3904
 email: sales@hellermannnyton.ca

HellermannTyton Mexico

Anillo Periferico Sur 7980 Edificio 2-D
 Parque Industrial Tecnologico II
 Tlaquepaque, Jalisco, Mexico 45601
 Phone: 011-52-33-3-133-9880
 Fax: 011-52-33-3-133-9861
 email: info@hellermannnyton.com.mx

ISO 9001:2000 Certified