


**KEMET Part Number: PEH169PJ4470QB2**  
(A472MK472Q100A)

PEH169\_105, Aluminum Electrolytic, 105C, 4,700 uF, -10/+30%, 100 VDC, -40/+105C



General Information	
<b>Supplier:</b>	KEMET
<b>Series:</b>	PEH169_105
<b>Dielectric:</b>	Aluminum Electrolytic
<b>Description:</b>	Screw Terminal, Aluminum Electrolytic
<b>RoHS:</b>	Yes
<b>Notes:</b>	Dimensions D And L Include Slewing. M5. MS = M12x16

Dimensions	
<b>D</b>	51.6mm +/-1mm
<b>L</b>	95.5mm +/-1mm
<b>T</b>	4.9mm NOM
<b>S</b>	22mm +/-0.5mm
<b>F</b>	15mm +/-0.5mm
<b>DT</b>	15mm NOM
<b>G</b>	13mm NOM
<b>LT</b>	103.4mm +/-1mm
<b>Z</b>	13mm NOM

Specifications	
<b>Capacitance:</b>	4,700 uF
<b>Capacitance Tolerance:</b>	-10/+30%
<b>Voltage DC:</b>	100 VDC
<b>Temperature Range:</b>	-40/+105C
<b>Rated Temperature:</b>	105C
<b>Life:</b>	8000 Hrs (Rated Voltage And Ripple Current At 105C)
<b>Resistance:</b>	26 mOhms (100Hz 20C), 17 mOhms (100kHz 20C)
<b>Ripple Current:</b>	7.7 Amps (100Hz 105C), 37.1 Amps (10kHz 50C), 27.6 Amps (10kHz 40C)
<b>Leakage Current:</b>	5410 uA (5min 20C)
<b>Inductance:</b>	16 nH (ESL)

Packaging Specifications	
<b>Weight:</b>	240 g
<b>Slewing:</b>	Yes
<b>Packaging:</b>	Bulk, Bag
<b>Packaging Quantity:</b>	20