


# Pin strip - PST 1,3/ 4-LV-5,0 L18 - 1703057

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



## Key Commercial Data

Packing unit	100 STK
Minimum order quantity	1000 STK
GTIN	 4 046356 634083
GTIN	4046356634083

## Technical data

### Dimensions

Pitch	5 mm
Dimension a	15 mm
Constructional height	11.2 mm

### General

Range of articles	PST 1,3/...-LV
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE
Nominal current I <sub>N</sub>	13.5 A
Color	black
Number of positions	4

### Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Approvals

Approvals

## Pin strip - PST 1,3/ 4-LV-5,0 L18 - 1703057

### Approvals

Approvals


EAC

---

Ex Approvals

---

### Approval details

EAC		B.01742
-----	---	---------

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>