

5

4

3

2

1

受控 CONTROLLED DOCUMENT

编号 P/N	CPN 17-CUST	版本 Rev	01	日期 Rel'd Date	SEP 14,09
-----------	-------------	-----------	----	------------------	-----------

Description: N-male 3 pc crimp RG8X

Part No: CPN17

Application: For RG8X Cable

Crimp Tool: 24-312

Impedance: 50 Ohms

Frequency Range: 0-11 GHz

Material: Crimp Sleeve Brass Nickel plated
Contact Brass Ni/Au plated
Body Brass Nickel plated
Coupling Nut Brass Nickel plated

RoHS Compliance: Yes

Technical Detail: Refer to Emerson Document P/N 26-0000

DRAWING NO.

CPN17-CUST

REVISIONS

OFFICAL RELEASE

01

08-17-09	J	T	T	<i>Betty</i>	2009.09.0 808:53:38 +0800C
----------	---	---	---	--------------	---

D

D

C

C

B

B

A

A

13.2
(.522)

∅ 6.6
(.261)

∅ 7.5
(.296)

20.3
(.800)

∅ 1.65
(.065)

∅ 3.07
(.121)

32
(1.264)

∅ 4.4
(.173)

∅ 5.7
(.224)

∅ 19.5
(.768)

DIM OUTLINE

TOLERANCE UNLESS OTHERWISE SPECIFIED		DRAWN BY	DATE
DECIMALS	mm	JEAN.JIN	08-17-09
X	± 0.5	CHECKED BY	DATE
X.X	± 0.2	TERRY.W	08-17-09
X.XX	± 0.1	APPROVED BY	DATE
ANGLES	± 0.5°	THOMAS	08-17-09
		U/M	mm

CUSTOMER COPY

TITLE
N-MALE 3 PC CRIMP RG8XSHEET
1 OF 1DRAWING NO.
CPN17-CUSTSIZE
ATHIS DRAWING WAS PRODUCED BY COMPUTER,
DO NOT SCALE DRAWING OR UPDATE MANUALLY.

5

4

3

2

1