

DENSEI-LAMBDA

SPECIFICATIONS

MB SERIES

G031-01-01D

Items		Model					
		MB1206	MB1210	MB1216	MB1220	MB1236	
1	Rated Voltage (AC,DC)	-	250V				
2	Rated Current (AC,DC) (*1)	A	6	10	16	20	36
3	Test Voltage (terminals to case, 1min AC)	-	2500V(20mA) at 25°C , 70% RH				
4	Isolation Resistance (terminals to case, 500V DC)	-	100MΩ min at 25°C , 70% RH				
5	Leakage Current	125V,60Hz	0.5mA max				
		250V,60Hz	1mA max				
6	DC Resistance (both line)	mΩ	140 max	50 max	34 max	20 max	9 max
7	Temperature Rise	-	40°C Max				
8	Operating Temperature	-	-25°C ~ +85°C				
9	Operating Humidity	-	30% ~ 95% RH (No Dewdrop)				
10	Storage Temperature	-	-40°C ~ +85°C				
11	Storage Humidity	-	10% ~ 95% RH (No Dewdrop)				
12	Vibration	-	10~55~10 Hz , Amplitude (Sweep for 1min) 1.5mm(88.3m/s ² max), X,Y,Z 2h each				
13	Safety Standards	-	UL , CUL , EN Approved				
14	Weight	g	190 typ	220 typ	310 typ	530 typ	660 typ

NOTE

*1 Value for $T_a \leq 35^\circ\text{C}$
 For $T_a > 35^\circ\text{C}$, derate
 according to the derating curve
 shown on the right.

