

Documentation

Installation Guide

Application

- Debug hardware
- Debug software
- Flash programming

Warranty: 1 year from date of purchase

Part #:701250

SPI510 ISA JTAG Emulator with Variable Voltage Pod



SPI510 ISA JTAG Emulator with Data Logging

Hardware Features

- Supports Texas Instruments Digital Signal Processors and Microcontrollers with **JTAG** interface(C2xx, C24x, F28xxx, F240x, VC33, C4x, C5x, C54xx, C55xx, C6xxx, C64xx, TMS470, OMAP™, DaVinci™)
- Requires 1 ISA slot inside PC
- Emulator pod powered by ISA adapter
- Supports processors with JTAG levels between 1-5 volts

Software Features

- Compatible with the Full License of Code Composer Studio from Texas Instruments *(Not compatible with the DSK/eZdsp/EVM Tools versions of Code Composer Studio)*
- Compatible with Win 98 ME, NT, 2000, XP
- Compatible with SDFlash programming utility from Spectrum Digital

What's Included

- SPI510 ISA Emulator adapter
- SPI510/525 Emulator Pod
- CD-ROM with drivers

Do You Need ?

- Code Composer Studio
- Target board (EVM, DSKs, eZdsp)
- 4 Channel JTAG Expander
- 14-20 pin Adapter