


## TAA-Compliant Protect It! 8-Outlet Computer Surge Protector, 8-ft. Cord, 3150 Joules, Tel/Modem/Fax Protection

MODEL NUMBER: TLP808TELTAA



### Highlights

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 8 outlets / 8-ft. cord
- 3150 joule rating
- Modem/fax surge protection

### Package Includes

- TLP808TELTAA Surge Suppressor
- 6-ft. telephone cord
- Instruction manual with warranty information

### Description

Tripp Lite's TLP808TELTAA surge suppressor is compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases. It has 8 outlets, an 8-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 3150 joules to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. \$150,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

### Features

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 8 outlets with integrated child safety covers
- 8-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks (1 in/2 out) prevent surges from damaging your modem/fax/phone equipment; 6-ft. telephone cord included
- Surge suppression rating: 3150 joules
- Automatic shutoff cuts power to all outlets when protection circuit is compromised
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$150,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- Lighted power switch

## Specifications



| <b>OVERVIEW</b>                              |  |
|--|--|
| UPC Code                                     | 037332159267   |
| <b>OUTPUT</b>                                |  |
| Frequency Compatibility                      | 60 Hz  |
| Output Receptacles                           | (8) 5-15R  |
| Output (Watts)                               | 1800W  |
| Circuit Breaker (amps)                       | 15   |
| Transformer Accommodation                    | Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 6 transformers total |
| Outlet Safety Covers                         | Includes built-in sliding outlet safety covers   |
| Outlet Orientation                           | Single row of 5, plus a second row of 3 for transformer accommodation  |
| Right-Angle Outlets                          | No   |
| <b>INPUT</b>                                 |  |
| Nominal Input Voltage(s) Supported           | 120V AC  |
| Recommended Electrical Service               | 120V (110-125V)  |
| Input Connection Type                        | NEMA 5-15P   |
| Input Plug Features                          | Space-saving right angle input plug  |
| Input Cord Length (ft.)                      | 8  |
| Input Cord Length (m)                        | 2.44   |
| Input Cord Gauge Type                        | 14 gauge, SJT  |
| Voltage Compatibility (VAC)                  | 120  |
| Right-Angle Plug                             | Yes  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |  |
| Switches                                     | Combination AC circuit breaker and 2-position red illuminated on/off power switch                                    |
| Diagnostic LED Details                       | Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status                            |
| <b>SURGE / NOISE SUPPRESSION</b>             |  |
| AC Suppression Joule Rating                  | 3150   |
| AC Suppression Response Time                 | < 1 ns   |
| Protection Modes                             | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                   |
| Clamping Voltage (RMS)                       | 150  |
| UL1449 Let Through Rating                    | 400 L-N, 500 L-G, 500 N-G  |
| EMI / RFI Filtering                          | Up to 40 dB  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

| <b>DATALINE SURGE SUPPRESSION</b>   |   |
|-------------------------------------|---|
| Telephone/DSL Protection            | Yes   |
| Telephone/DSL Protection Details    | 1 line  |
| Cable (Coax) Protection             | No  |
| Network (Ethernet) Protection       | No  |
| <b>PHYSICAL</b>                     |   |
| Shipping Dimensions (hwd / in.)     | 11.00 x 7.30 x 1.90   |
| Shipping Dimensions (hwd / cm)      | 27.94 x 18.54 x 4.83  |
| Shipping Weight (lbs.)              | 0.00  |
| Shipping Weight (kg)                | 0.00  |
| Unit Dimensions (hwd / in.)         | 3.9 x 2.2 x 10.5  |
| Unit Dimensions (hwd / cm)          | 9.8 x 5.6 x 26.6  |
| Unit Weight (lbs.)                  | 1.3   |
| Unit Weight (kg)                    | 0.59  |
| Material of Construction            | Plastic   |
| Integrated Keyhole Mounting Tabs    | Keyhole mounting slots enable wall mounting   |
| Receptacle Color                    | Cool gray 1c  |
| Color (AC Line Cord)                | Cool Gray 1C  |
| Anti-Microbial Protected            | No  |
| <b>SPECIAL FEATURES</b>             |   |
| Additional Information              | Pair of phone line output jacks serve as a line splitter to enable the protection of two devices sharing a single dialup phone line |
| <b>CERTIFICATIONS</b>               |   |
| UL1449 3rd Edition (AC Suppression) | UL1449 3RD EDITION  |
| UL1363 (Power Tap)                  | UL1363  |
| UL497A (Communications)             | UL497A  |
| FCC Part 68 (Communications)        | FCC Part 68   |
| cUL / CSA (Canada)                  | cUL   |
| Industry Canada (Communications)    | Industry Canada   |
| Approvals                           | Exceeds IEEE 587 category A&B specifications  |
| <b>WARRANTY</b>                     |   |
| Product Warranty Period (Worldwide) | Lifetime limited warranty   |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|   |  |
|---|--|
| Connected Equipment Insurance<br>(U.S., Canada & Puerto Rico) | \$150,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a> |
|---|--|

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:  
<https://www.tripplite.com/products/product-certification-agencies>