

Electronic housing - BC 161,6 OT 000022 KMGY - 2201454

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Installation component housing, length: 89.7 mm, Upper part, color: light gray, width: 161.6 mm, height: 62.2 mm

Why buy this product

- Item is from the BC product range
- Conforms to DIN EN 43880
- Tool-free mounting
- Available in overall widths from one to nine width units (17.8 mm ... 161.6 mm)
- Inflammability class V0 according to UL 94
- Variety of connection technologies
- Can be mounted on the DIN rail or the wall
- Optional with bus connector for DIN rail mounting



Key Commercial Data

Packing unit	10 STK
Minimum order quantity	500 STK
GTIN	
GTIN	4046356806237

Technical data

General

Housing type	Installation component housing
Housing material	Polycarbonate
Color (RAL)	light gray (7035)

Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
---------------------------------	--

Dimensions

Length	89.7 mm
--------	---------

Electronic housing - BC 161,6 OT 000022 KMGY - 2201454

Technical data

Dimensions

Constructional height	62.2 mm
Width	161.6 mm
Depth	89.7 mm

Technical data

Power dissipation without gap	16.95 W
-------------------------------	---------

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals

Approvals

Approvals

UL Recognized / EAC

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 240868
---------------	--	---	---------------

EAC			B.01742
-----	--	--	---------