


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 50.2              |
| B   | 1 3/4-18NS-2B     |
| C1  | 21.5              |
| C2  | 16.6              |
| D   | 43.3              |
| E   | 58                |
| F   | 66                |

| NO. | BESCHREIBUNG / DESCRIPTION          |
|-----|-------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN |
| 3   | DICHTKÖRPER / GROMMET               |
| 4   | ENDRING / ENDRING                   |
| 5   | KONTAKTSTIFT/ CONTACT PIN           |
| 7   | ZYLINDERGHÄUSE / BARREL             |
| 9   | ÜBERWURFMUTTER / COUPLING NUT       |
| 12  | ENDGEHÄUSE / ENDBELL                |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

| Material Specification: |                                |
|-------------------------|--------------------------------|
| Shell Material:         | Aluminium alloy                |
| Shell Plating:          | Black Zinc Cobalt (conductive) |
| Insulator Material:     | Neoprene                       |
| Contact Material:       | Copper alloy                   |
| Contact Plating:        | Hard silver                    |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m

drawing for  
 CUSTOMER



description CA3108E28-21P-F80-A206  
 Plug 90°  
 Endbell with clamp and bushing  
 AWG Crimp / Pin / Layout: 28-21

© All rights reserved. Reproduction or issue to third in any form  
 whatever is only permitted with written authorization of ITT Cannon

page 1/1  
 revision 769 16. Jul 18