

Ferrule - A 95 -40 - 3241242

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ferrule, sleeve length: 40 mm, length: 40 mm, color: silver

Why buy this product

- The ferrules without plastic sleeve are made from soft tin-plated electrolytic copper

Key Commercial Data

Packing unit	100 STK
Minimum order quantity	100 STK
GTIN	
GTIN	4046356908153

Technical data

Dimensions

Length (b)	40 mm
Maximum stripping length	40 mm
Sleeve length	40 mm
Inner dimension of the insulating collar (d)	17 mm
Ferrule diameter	14.5 mm
Sleeve wall thickness	0.4 mm

Ambient conditions

Short-term temperature	120 °C
Max. permanent temperature	105 °C

General

Note	These ferrules are not included in DIN 46228-1: 1992-08
Color	silver
Material	CU-DHP

Ferrule - A 95 -40 - 3241242

Technical data

General

Coating	tin-plated (galvanic)
---------	-----------------------

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>