



- 1 BRASS PER AMP SPECIFICATION 100-110 1/2 HARD OR BRASS PER AMP SPECIFICATION 100-380 1/4 HARD.
- 2 CONTACT MATING AREA MEETS THE PERFORMANCE REQUIREMENTS OF TE CONNECTIVITY PRODUCT SPECIFICATION 108-1957; BASED ON TELCORDIA GR-1217-CORE, APPLICATIONS IN UNCONTROLLED ENVIRONMENTS.
- 3 RECOMMENDED HOLE SIZE 3.1mm.

11.00 [0.433] 120759-2  
A PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN	DK SCHRUM	25AUG99
DIMENSIONS: mm [INCHES]		CHK	HW ANDREWS	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	HW ANDREWS	
0. PLC	± -	NAME	GUIDE PIN, STATIC DISCHARGE	
1. PLC	± -	PRODUCT SPEC		
2. PLC	± 0.13 [0.005]	APPLICATION SPEC		
3. PLC	± -	SIZE	A1	00779
4. PLC	± -	WEIGHT	120759	
ANGLES	± -	RESTRICTED TO		
MATERIAL	FINISH	CUSTOMER DRAWING	SCALE	8:1
1	2		SHEET	1 OF 1