

1281 (7/68)

APPLICATOR PARTS LIST

TYPE LENGTHWISE
Splice CONN. (THRU.)

AMP INCORPORATED
HARRISBURG, PENNA.

REV N ECN A-272490 JEG CE 10/6/80
REV ECN A-377392 LA 7-17-92

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	
1	WIRE CRIMPER 2-40 4065	1	30944	42	Feed Plate	1	376975	
2	INS. CRIMPER			43	Spring-Slide	1	274017-7	
3	ANVIL	1	374368	44	Feed Plate Retainer	1	376975	
4	ANVIL SPACER			45	Feed Holder	1	377192	
5	SHEAR BLADE	1	376734	46	Feed Holder Base	1	472114	
6	REAR ANVIL PLATE-Feed	1	472045	47	Pin (Feed Holder Base)	1	377584	
7	SHEAR BLADE SPACER			48	Front Feed Holder	1	376976	
8	FRONT SHEAR PLATE			49	Rear Feed Holder	1	376977	
9	REAR ANVIL SPACER PLT.			50	Feed Link	1	374837	
10	FRONT ANVIL SPACER PLT.			51	Roll Pin 1/8 Dia. x 1/2 Lg.	1	5-21028-1	
11	TOOL SPACER			52	Cotter Pin 3/32 Dia. x 1/2 Lg.	1	2-22170-7	
12	CRIMP SPACER			53				
13	FRONT STRIP GUIDE			54				
14	REAR STRIP GUIDE			55	Ⓢ Sq. Hd. Set Scr. -Depressor	1	21077-7	
15	RAM	1	471057	56	Ⓢ Nut Jam	1	22202-3	
16	TOOL HOLDER			57				
17	ADJ. CRIMP MOUNT			58				
18	ADJ. BLOCK			59				
19	APPLICATOR MOUNT ASSY.	1	473993	60				
20	BASE PLATE			61				
21	BASE BLOCK			62				
22	STRIP GUIDE PLATE			63				
23	ANVIL HOLDER	1	374348	64	1" AIR FEED ASSY	1	690021-1	
24	AUX. ANVIL HOLDER	1	378975	65				
25	WIRE GUIDE	1	376945	MISCELLANEOUS				
26	STRIPPER	1	810995-2	66	LUBRICATOR ASSY	1	465184-2	
27	SPACER STR.	1	385530	67	SYNTHETIC OIL	REF	A52931-2	
28	STRIPPER MOUNT BRACKET			68				
29	STRIPPER BUSHING			69				
30	STOCK DRAG	1	376972	70				
31	STOCK DRAG HANDLE NUT	1	21022-4	71				
32	STOCK DRAG STUD			72	1" AIR FEED ASSY		690021-1	
33	STOCK DRAG SPRING 373469	1	373469	REV. REVISION RECORD				
34	STOCK DRAG ADJ. SCREW			REV.	REVISION RECORD	DATE	BY	ECN
35	FEED FINGER HOLDER			C	Revised & Retyped	11-11-65	ADD	
36	FEED FINGER	1	376978	D	PER ECN	7-2-71	FR	6753
37	FEED FINGER Spring	1	376661	DI	DATE TERM # 40651 & 60768	1-28-71	W	L-7314
38	FEED FINGER SPACER			E	REV PER ECN	3-26-71	W	L-8202
39	BASE CASTING	1	510238	F	AIR FEED WAS MECH -2	10-12-72	ED	L-9224
40	GUARD 460582-4	1	376975	G	REV PER ECN	4-4-73	W	L-9653
41				H	REV PER ECN	7-11-73	W	R-642
				J	ITEM 40 WAS -1	4-5-76	W	R-1631
				K	REV PER ECN	10-17-77	W	R-220

CRIMPING DATA			TERMINALS
TO APPLY TERMINAL			40862
WIRE SIZE CRIMP HEIGHT			41080
GROUP	40862	41313	41489
CRIMP SIZE TYPE FEED			
WIRE	.090	F	
INSUL.			.093
SLEEVED			
WIRE RANGE		WIRE RANGE	.012
800-2500		1400-3200 OIA	41215
EXPLODED VIEW			
A-6010-3 A-6010-4			
REMARKS:			
Out Away Anvil			
<p>⚠ TERM FEED OF 60933-2 IS .152 ALL OTHERS ARE .093</p>			
<p>Ⓢ DENOTES WEARING PARTS RECOMMEND PURCHASE REPLACEMENT</p>			
THIS APPLICATOR IS TO BE USED ON			
AMP-O-LECTRIC 1-471273-2			
AMP MODEL AIR FEED			
SERIAL NO.			DIST. 4
DATE SHIPPED			DESIGNED P.D. 1-7-6
CUSTOMER NAME AND ADDRESS			CHK'D. MT 3-7-6
APPLICATOR NUMBER			
REV. 670953			

L1 REV PER ECN SUPP R2576 7-28-78 KS
M REV PER ECN 4100 4/28/80 R3578

K1 ADD TERM 16065 PER 3-78 SA
L REV PER ECN 4-5-76

REV PER ECN R-1585