


## FL SFP SX

Order No.: 2891754



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2891754>

Small form factor pluggable module is a pluggable input/output module for FO and is used in Gigabit Ethernet. Glass fiber module with a wavelength of 850 nm (short).

Commercial data	
GTIN (EAN)	 4 046356 166782
sales group	K000
Pack	1 pcs.
Customs tariff	85176200
Catalog page information	Page 185 (AX-2009)

### Product notes

WEEE/RoHS-compliant since:  
12/08/2009



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>Interfaces</b>	
Interface	Ethernet FO
No. of ports	1
Type of connection	1 LC socket at the SFP module, 1000 Mbps
Transmission physics	Multimode glass fiber

Transmission speed	1 GBit/s
Transmission length	550 m (Glass fiber 50/125)
	300 m (Glass fiber 62.5/125)
Signal LEDs	depending on the Factoryline device

**Function**

Basic functions	SFP module as FO port
Status and diagnostic indicators	via a Factoryline device

**General data**

Ambient temperature (operation)	-40 °C ... 85 °C (no condensation)
Ambient temperature (storage/transport)	-40 °C ... 85 °C (no condensation)
Permissible humidity (operation)	30 % ... 95 % (no condensation)
Permissible humidity (storage/transport)	30 % ... 95 % (no condensation)
Air pressure (operation)	86 kPa ... 108 kPa (1500 m above sea level)
Air pressure (storage/transport)	66 kPa ... 108 kPa (3500 m above sea level)
Housing material	Metal

**Certificates / Approvals**



Certification

CUL, DNV, UL

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;