1 MATES WITH HOUSING 480285.
2 PARTS COMPLY WITH AMP SOLDERABILITY SPEC 109-11-3.





RECOMMENDED LAYOUT FOR .125 THICK P.C. BOARD

1. MATES WITH HOUSING 480285.
2. PARTS COMPLY WITH AMP SOLDERABILITY SPEC. NO. 109-11-3

Unpublished copy not to be reproduced nor published without written permission of AMP Incorporated

LTR	REVISION RECORD	DR	CHK	DATE
K	RESTORED	BKD	RS	3/28/85
K	REV. PER M-7375	SS	CM	8-27-84
J	2.50" TOOLING & REF M-7285	DAS	DH	4/11/83
H	ADDED NOTE 3, M-6694	MF	DH	4-30-81
G	REV. TAIL LENGTH M-5334	MF	DH	3-24-77
F	REVISED M-4161	MF	DH	3-7-77
E	ECN M-3871	BRN	DH	9-10-76
D	ECN M-3452	GY	RCF	5/18/76
C	ECN M-3156	BC	MW	9/4/75
B	SUPERSEDED BY 350219 ADDED COLORS			6/2/75

LTR	DESCRIPTION	REQUIRED PER ASSEMBLY
M	OBSOLETE -2 PER ECN CM-2709	
L	OBSOLETE 1-1, 1-2, 2-1, 2-2, 3-1, 3-2, 4-1, 4-2, 5-1, 5-2, 6-1, 6-2, 7-1, 7-2, 8-1, 8-2, 9-1, 9-2 CM 4/73	

ASSEMBLY NO.	HSG. MATL & COLOR	PIN MATL & FINISH
350219-1	NYLON - NATURAL	copper alloy · PRE-TIN

©1973 BY AMP INCORPORATED. ALL RIGHTS RESERVED.
AMP PRODUCTS COVERED BY PATENTS AND/OR PATENTS PENDING.

CUSTOMER COPY REFERENCE ONLY

DR 9. E. 6-13-73
CHK E. G. 6-14-73
DE
APP Emp. P. Kawchuga 6/14/73

MATERIAL AND FINISH: SEE TABLE
WIRE — RANGE — INSULATION: —
TOLERANCE EXCEPT AS NOTED ±.015 ±1°0'
SCALE —

AMP INCORPORATED HARRISBURG, PENNA.
CLASS H
TYPE H
LOC CM B NO 350219 REV M

NAME 10 CIRCUIT MATE-N-LOK P.C. BOARD HEADER

SIZE A
SHEET 1 OF 1
PRINT 53

DIMENSIONS IN INCHES. DO NOT SCALE PRINT.

AMP 1253 REV 11/65