

1

2

3

4

5

6

7

A

A

Panel Thickness  
Screw L=5.0 For Panel Thickness Under 1.2mm  
Screw L=6.0 For Panel Thickness Between 1.2-2.0mm

B

B

**NOTES:****MATERIAL**

1. Insulator Material: Black, NYLON+G/F
2. Contact Material : Copper Alloy
3. Plating : Gold Plating
4. Waterproof Rate: IP67
5. Do Mating Test After Glued
6. Applicable Wire Range: 24AWG~28AWG
7. LOGO

C

C

Recommended Panel Cut-Out

D

D

E

E

F

F

G

G

**RoHS compliant**

Scale	1:1					Date	Name	Customer-No.		
TOLERANCE					Drawn	30.12.2008	JACK			
X.X	±0.25				Approved	30.12.2008	Hellwig	ASSMANN WSW-No.		
X.XX	±0.10							<b>A-HDF 26 LL-WP</b>		
X.XXX	±0.05							Drawing-No.		
DIM	TOL							<b>ASS 3279 CO</b>	rev01	
ANGLE	±1°									
X.X°	±X°	①	Drawn	30.12.2008				JACK		
Angle	TOL	Id.	Modification	Date	Name			Replace	Sheet	

H

H

1

2

3

4

5

6

7