

## Cable gland - G-ESISEC-M63-L68L-NEPDS-S - 1415170

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Nickel-plated brass, Application: Ex, External cable diameter 34 mm ... 48 mm, Shielding: Yes, Connecting thread: M63, Color: silver

The figure shows the G-ESIS-M25-M68N-NEPDS-S version



### Key Commercial Data

Packing unit	1 pc
Custom tariff number	74199990
Country of origin	Germany

### Technical data

#### Dimensions

Length	61 mm
Length without connecting thread	46 mm
Connecting thread diameter	63 mm
Wrench size, union nut	68 mm
Wrench size, support	68 mm
Hexagon angular dimension GRP	75 mm
Length of the connecting thread	15 mm
External cable diameter	34 mm ... 48 mm

#### Ambient conditions

Degree of protection	IP66
	IP68
Ambient temperature (operation)	-40 °C ... 75 °C

# Cable gland - G-ESISEC-M63-L68L-NEPDS-S - 1415170

## Technical data

### General

Cable gland material	Nickel-plated brass
Seal material	EPDM
O-ring material	EPDM
Thread type on connection side	M63
Torque	40 Nm (Support)
Tightening torque, union nut	40.00 Nm
Color	silver
ATEX	II 2 G/D EEx e II IP68
IECEX	Ex e IIC Gb, Ex tb IIIC Db

## Classifications

### eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109

### ETIM

ETIM 5.0	EC000441
----------	----------

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / GL / cULus Recognized

---

#### Ex Approvals

ATEX / IECEX / EAC Ex

---

#### Approvals submitted

---

### Approval details

UL Recognized
---------------

# Cable gland - G-ESISEC-M63-L68L-NEPDS-S - 1415170

## Approvals

cUL Recognized

GL

cULus Recognized

## Drawings

Dimensional drawing

