

## Specification Sheet

Part Number: T50R5M4



Standard Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Green, 1000/pkg

|                     |  |
|---------------------|--|
| Article Number      | 111-04854  |
| Type                | T50R   |
| Color               | Green (GN)   |
| Features & Benefits | <ul style="list-style-type: none"><li>• Inside serrations allow for strong hold on cables and wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul> |
| Quantity Per        | bag  |

### Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

|  |   |
|--|---|
| <b>Short Description</b>                   | Standard Cable Tie, 8" Long, UL Rated, 50lb Tensile Strength, PA66, Green, 1000/pkg |
| <b>Global Part Name</b>                    | T50R-PA66-GN  |
| <b>Minimum Tensile Strength (Imperial)</b> | 50.0  |
| <b>Minimum Tensile Strength (Metric)</b>   | 225.0   |
| <b>Length L (Imperial)</b>                 | 8.0   |
| <b>Length L (Metric)</b>                   | 202.0   |
| <b>Identification Plate Position</b>       | none  |
| <b>Releasable Closure</b>                  | No  |
| <b>Tie Closure</b>                         | plastic pawl  |
| <b>Variant</b>                             | Inside Serrated   |
| <b>Width W (Imperial)</b>                  | 0.18  |
| <b>Width W (Metric)</b>                    | 4.6   |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.06  |
| <b>Bundle Diameter Min (Metric)</b>        | 1.5   |
| <b>Bundle Diameter Max (Imperial)</b>      | 1.97  |
| <b>Bundle Diameter Max (Metric)</b>        | 50.0  |

|                             |     |
|-----------------------------|-----|
| <b>Thickness T (Metric)</b> | 1.2 |
|-----------------------------|-----|

|                 |                      |
|-----------------|----------------------|
| <b>Material</b> | Polyamide 6.6 (PA66) |
|-----------------|----------------------|

|                          |      |
|--------------------------|------|
| <b>Material Shortcut</b> | PA66 |
|--------------------------|------|

|                    |             |
|--------------------|-------------|
| <b>US MIL SPEC</b> | SAE-AS33671 |
|--------------------|-------------|

MS3367-1-5  
**Flammability**

|          |                     |
|----------|---------------------|
| UL 94 V2 | <b>Halogen free</b> |
|----------|---------------------|

|     |                                       |
|-----|---------------------------------------|
| Yes | <b>Operating Temperature (Metric)</b> |
|-----|---------------------------------------|

|                                  |                       |
|----------------------------------|-----------------------|
| -40°F to +185°F (-40°C to +85°C) | <b>ROHS Complaint</b> |
|----------------------------------|-----------------------|

|     |  |
|-----|--|
| Yes | <b>Certification/Specification WEB</b> |
|-----|--|

|                                |                           |
|--------------------------------|---------------------------|
| UL-ZODZ.E64139 CAGE Code 53421 | <b>UL Recognized (US)</b> |
|--------------------------------|---------------------------|

|     |                                  |
|-----|----------------------------------|
| Yes | <b>UL Listed (US and Canada)</b> |
|-----|----------------------------------|

|     |                                      |
|-----|--------------------------------------|
| Yes | <b>UL Recognized (US and Canada)</b> |
|-----|--------------------------------------|

|     |  |
|-----|--|
| Yes |  |
|-----|--|

|                                   |      |
|-----------------------------------|------|
| <b>Package Quantity(Imperial)</b> | 1000 |
|-----------------------------------|------|

|                                  |      |
|----------------------------------|------|
| <b>Package Quantity (Metric)</b> | 1000 |
|----------------------------------|------|

**Customs Number**

3926909987

---

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)