

## Sleeve housing - HC-B 32-TFQ-80/O1PG36S X - 1646036

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

HEAVYCON B32 sleeve housing, for double locking latch, height: 80 mm, with 1 x Pg29 gland, lateral cable outlet

### Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	460.8 GRM
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### Dimensions

Height	80 mm
Width	79 mm
Length	94 mm

#### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Note	For contact inserts HC-B32, DD144, M
Design	B32
Housing type	Sleeve housings
Locking type	For double locking latch
Cable exit	Lateral
Screw connection	None
Type of the screw connection	1x Pg36
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, gray

### Classifications

#### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424

## Sleeve housing - HC-B 32-TFQ-80/O1PG36S X - 1646036

### Classifications

#### eCl@ss

eCl@ss 6.0	27143424
eCl@ss 7.0	27440209

#### ETIM

ETIM 3.0	EC000437
ETIM 4.0	EC000437
ETIM 5.0	EC000437

#### UNSPSC

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502