

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

LOC

DIST

REVISIONS

© COPYRIGHT 20

TE

ALL RIGHTS RESERVED.

GP

00

P

LTR

DESCRIPTION

DATE

DWN

APVD

B

REV PER ECO-11-007678

18MAY2011

RG

DO

DRILLED HOLE
 $\varnothing .0453 \pm .001$
 AFTER PLATING
 $\varnothing .043 / .037, 10X$

4X .100

.400 TRACE

.300

.400

CROWN

.500

.410

.020 BOARD STAND-OFF

5

(.150)

(.300)

4X .100

1. PART NUMBER CHANGES AND/OR DESIGN CHANGES AFFECTING ITEM INTERCHANGEABILITY REQUIRE PRIOR TE APPROVAL AND AUTHORIZATION BY REVISION TO THIS DRAWING.

2. ITEMS PROVIDED TO THIS SPECIFICATION SHALL BE IDENTIFIED ON CONTAINER WITH THE FOLLOWING INFORMATION, PART NUMBER AND DATE CODE OF MANUFACTURE.


3. MATERIAL:
 INSULATOR - POLYESTER, GLASS FILLED, UL94 V-O RATED, COLOR: BLACK
 MODULE - METAL CASTING
 CROWN - BeCu
 CONTACT - BRASS

4. FINISH:
 INSERT - SILVER PLATED .000200 MIN THK. OVER NICKEL .000040 MIN THK.
 CROWN - GOLD PLATED .000030 MIN THK. OVER NICKEL .000040 MIN THK.

5 A FIVE POUND (5lb) FORCES REQUIRED TO CORRECTLY SEAT THE CONNECTOR WITH PLATED THRU HOLES LESS THEN $\varnothing .040$.

6643232-1

PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 18MAY2011 LOVATO/GRZYBOWSKI	 TE Connectivity	
DIMENSIONS: INCHES		CHK D. ORRIS		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 18MAY2011 CHAU/ORRIS	NAME ICCON SOCKET, PARALLEL 10 PIN FOOTPRINT, SOLDER STYLE	
0 PLC ±-		PRODUCT SPEC	-	
1 PLC ±-		APPLICATION SPEC	-	
2 PLC ±-		WEIGHT	-	
3 PLC ±.020		CUSTOMER DRAWING	SCALE 4:1	SHEET 1 OF 1
4 PLC ±-		FINISH	REV B	
ANGLES ±.5				
MATERIAL -			SIZE A3	CAGE CODE 00779
			DRAWING NO C-6643232	RESTRICTED TO -

1470-19 (3/11)

Pro/ENGINEER DRAWING